

TEC-GUARD

EXTREME



TEC-GUARD EXTREME HIGH PERFORMANCE GEAR OILS

TEC-GUARD® Extreme High Performance Gear Oils are premium quality gear oils blended from select base oils and an advanced additive package, they are designed to meet the challenges of higher speeds, higher torque, and heavier loads.

TEC-GUARD® Extreme 85W-140 Gear Oil meets the requirements of API GL-5 and API MT-1 for use in passenger cars, light-duty trucks as well as axles of heavy-duty trucks, off-road equipment, tractors and outboard motors. Always consult your owner's manual for specific recommendations.

- Excellent rust and corrosion protection
- Thermal stability and resistance to high temperature oxidation
- Outstanding protection against low speed/high torque wear and against high speed scoring
- Reduces wear and extends equipment life

Test Method		Product Numbers	
ASTM D1298A - API Gravity	23.5	Bulk	10419201985140
ASTM D92 - Flash Point, °C	220	Drum	10419211985140
ASTM D5949 - Pour Point, °C	-12	Pail	10419241985140
ASTM D445 - Viscosity @ 40° C, cST	370	Keg	10419221985140
ASTM D445 - Viscosity @ 100° C, cST	25.3	Tote	10419201985140
ASTM D2270 - Viscosity Index	100	4/1 Gallon	10419111985140
		2/2.5 Gallon	10419161985140
		12/1 Quart	10419261985140