



# TEC-GUARD



# EXTREME

## TEC-GUARD EXTREME HIGH PERFORMANCE FULL SYNTHETIC GEAR OILS

**TEC-GUARD® Extreme High Performance Gear Oils** are premium quality limited slip gear oils blended from synthetic base oils and an advanced additive package, they are designed to provide protection under severe operating conditions, reduce operating costs, and improve fuel economy.

**TEC-GUARD® Extreme Full Synthetic Limited Slip 75W-90 Gear Oil** meets the requirements of API GL-5, API MT-1, MIL-PRF-2105E and MIL-PRF-2105D for use in passenger cars, light-duty trucks, axles of heavy-duty trucks, off-road equipment, tractors and outboard motors with limited-slip differentials, manual transmissions and final drives. Meets Mack® GO-J, GO-H, GO-G, MIL-L-2105D, ArvinMeritor® O76-E requirements, always consult your owner's manual for specific recommendations.

- Enhanced Frictional Properties
- Resistant To Foaming
- Potential Extended Oil Drain/Service Intervals

Test Method		Product Numbers	
Specific Gravity @ 60°F	.875	Bulk	10421205375W90
ASTM D92 - Flash Point, °C	150	Drum	10421212575W90
ASTM D5949 - Pour Point, °C	-48	Pail	10419246375W90
ASTM D445 - Viscosity @ 40° C, cST	126	Keg	
ASTM D445 - Viscosity @ 100° C, cST	17.3	Tote	10421205375W90
ASTM D2270 - Viscosity Index	151		